



LTE Cat M1/NB2 with 2G Fallback

Rapid Installation

SOS Emergency Button

Water Resistant

OTA Control

Scheduled Report

Geo-fences

Motion Detection

Ignition Detection

Vibration Feedback

Low Power Alarm

Use with Animal Collars

Up to 10,000 Buffer Messages

GL320MG

LTE Cat M1/NB2 GNSS tracker with a user-friendly panic button for personal safety management and asset monitoring applications

93g (3.28oz)

39.9 × 26.7 × 77.9mm
1.57"(L) × 1.05"(W) × 3.07"(H)

-20°C ~ +60°C

Li-Polymer, 2600 mAh

Standby Time:

Without Reporting 480 Hours

5 Min Reporting 260 Hours

10 Min Reporting 300 Hours

The GL320MG is the LTE version of our best-selling GL300, which is the most popular series in our range of asset trackers with large deployments worldwide. It is used for a wide range of applications which require real-time location knowledge, such as private investigations, package delivery, temporary tracking of vehicles, long distance transportation, endurance racing and animal management. As one of the market leaders in reliable battery powered asset trackers, our products are targets for imitation, but we are happy to say that up to this day, our GL300 still leads the field in battery life and overall performance.



GL320MG

| Region | Network/Operating Band | GNSS Type | Position Accuracy (CEP) | Certificate |
|-----------|---|---------------------------------|-------------------------|-------------------|
| Worldwide | Cat M1: LTE-FDD:B1/B2/B3/B4/B5/B8/ B12/B13/B18/B19/B20/B25/B26/ B27/B28/B66/B85 Cat NB2: LTE-FDD:B1/B2/B3/B4/B5/B8/ B12/B13/B18/B19/B20/B25/B28/ B66/B71/B85 EGPRS: 850/900/1800/1900MHz | u-blox All-in-One GNSS receiver | Autonomous: < 2.5m | FCC, Verizon , IC |

Appearance**Interfaces**

| | |
|---|--|
| Digital Inputs | 1 positive trigger input for ignition detection 1 negative trigger input for normal use |
| Power Button | Power on and power off, can be disabled via air interface protocol |
| Function Button with Vibration Feedback | Emergency alert or instant geo-fence setting |
| Cellular Antenna | Internal only |
| GNSS Antenna | Internal only |
| LED Indicators | CEL, GNSS, PWR |
| USB Type-C Interface | Used for external power and configuration |

Air Interface Protocol

| | |
|---------------------|---|
| Transmit Protocol | TCP, UDP, SMS |
| Scheduled Report | Report position and status based on preset time intervals, distance, mileage or a combination of these settings |
| Geo-fences | Support up to 20 geo-fence regions |
| Low Power Alarm | Alarm when battery is low |
| Power On/Off Report | Report when the device is powered on and off |
| SOS/Emergency Alarm | SOS alarm via pressing function button |
| Special Alarm | Special alarm based on digital inputs |
| Motion Detection | Motion alarm based on internal 3-axis accelerometer |

Accessories



EBK

GL300 external battery kit

Parts list:

Pelican 1020 box

Power control unit with built-in motion sensor

External battery 17600 mAh

Wall charger for external battery

Frame and cables



GL-HM3G-V3

High quality magnetic holder

IP67 waterproof



Sheath

A sheath for holding GT301, GL300W or GL300M



Extension Cable

A USB Type-C cable which is used to wire out the interfaces on the connector of GL300 series Include: external charger, external battery, ignition detection, digital input

Debug Cable



USB Type-C Data Cable

It is used for configuration, firmware upgrade and debug.