

Unmanaged Industrial Switch

FNS100-224-AGB-SFP-A



Introduction

FNS100-224-AGB-SFP-A is a network unmanaged industrial Ethernet switch. Support 24 1000Mbps 2Port SFP electrical ports; this series of switches adopts low power consumption and fanless design to ensure no noise interference; At the same time, it supports -40~75°C working temperature and good EMC electromagnetic compatibility performance, ensuring stable work in harsh industrial environments, and building fast and stable network terminal interfaces for industrial applications such as factory automation, intelligent transportation, and video surveillance. Provide a safe and reliable solution for accessing the network.



Industrial-grade Design

- ▶ Metal casing, IP40 protection level
- ▶ Wide range operating temperature (-40°C~75°C)



Stability & Reliability

- ▶ Support low power consumption, fanless and silent design, metal shell, excellent on heat dissipation, stable quality



Standard & Convenience

- ▶ Support plug and play, flexible networking
- ▶ Support Rack-mounte

Unmanaged Industrial Switch

FNS100-224-AGB-SFP-A



Production Specification

Standard	
Model	FNS100-224-AGB-SFP-A
Item	Content
Ethernet Standard	IEEE802.3 10BASE-T; IEEE802.3i 10Base-T; IEEE802.3u;100Base-TX/FX; IEEE802.3ab 1000Base-T; IEEE802.3z 1000Base-X; IEEE802.3x,and,etc.
Industry Standard	EMI: FCC Part 15 Subpart B Class A, EN 55022 Class A EMC: IEC(EN)61000-4-2(ESD): ±6kV Contact discharge, ±8kV Air discharge IEC(EN)61000-4-3(RS) : 10V/m(80 ~ 1000MHz) IEC(EN)61000-4-4(EFT): ethernet port: ±2kV CM//±1kV DM. IEC(EN)61000-4-5(Surge): ethernet port: ±2kV CM//±1kV DM. IEC(EN)61000-4-6(Radio frequency conduction) : 3V(10kHz ~ 150kHz),10V(150kHz ~ 80MHz) IEC(EN)61000-4-16(Common mode conduction): 30V cont. 300V,1s IEC (EN)61000-4-8 Shock: IEC 60068-2-27 Freefall: IEC 60068-2-32 Vibration: IEC 60068-2-6

Switching Characteristics	
Model	FNS100-224-AGB-SFP-A
Item	Content
Buffer Memory	4Mbit
Transmission Method	Store-and-forward
Backplane Bandwidth	56G
Switching Latency	<10µs
MAC Address	8K
Power	
Item	Content
Input Voltage	Non POE: AC110-240V
Access Terminal	Phoenix terminal block

Unmanaged Industrial Switch

FNS100-224-AGB-SFP-A



Characteristics	Support dual power supply redundancy Support built-in over-current protection Support reverse connection protection with 4.0 A
------------------------	--

Operating Environment

Item	Content
Operating Temperature	-40 °C ~75°C
Storage Temperature	-40 °C ~85°C
Relative Humidity	5~95% (Non-condensing))

Interfaces

Item	Content
SFP Slot	Number: 2 Type: 1000BaseFX port (SFP slot)
Ethernet Port	Number: 24 Type: RJ45, 10/100/1000M automatic detection, full/half duplex MDI/MDI-X adaptive
Optical Fiber	Support single-mode/multi-mode fiber Multi-mode fiber: 550M Single-mode optical fiber: 20/40/60/80/100KM

Other

Model	FNS100-224-AGB-SFP-A
Item	Content
Shell	IP40 protection level, metal casing
Characteristic	Support plug and play, flexible networking
Dimension	442mm×194mm×44mm
Weight	<3Kg
Installation Method	Rack-mounte
Heat-dissipating Method	Natural cooling, no fan
LED	Power Indicator: PWR

Dimension (mm): 442×194×44mm

Order Information

Model	Description
FNS100-224-AGB-SFP-A	Unmanaged Industrial Switch: 24-Gigabit-Port RJ45+2Port SFP , Rak-mountable, Power supply: AC110-240V work temperature: -40°C-75°C