

Compact Multi-Interface Industrial Router

IWR202



5G Redcap & 4G



Passive PoE



Full Aluminum
Casing



2.4G WIFI



RS232 & RS485



DI & DO



Dual SIM



Industrial Design with Aluminum Housing

IP30



Aluminum housing, IP30, stable in harsh environments

Dual SIM Auto Switch



Dual SIM design, seamless signal, reliable backup switch

Multiple IoT Interfaces



Integrated RS232/RS485 and DI/DO interfaces

5G Redcap & 4G Support



Supports 5G Redcap and 4G CAT4/CAT6 with multi-band compatibility.

Item	IWR202
CPU	MTK7628A Industrial-grade Processor
DDR	128MB Industrial-grade RAM
Flash	32MB Industrial-grade Flash
Cellular	5G Redcap, 4G CAT6, 4G CAT4
WIFI	IEEE802.11b/g/n, 2.4GHz
Ethernet	1 x 100M WAN + 1 x 100M LAN
Serial	1 x RS232, 1 x RS485
I/O	1 x DO, 1 x DI
SIM	2 x 2FF SIM
VPN	Open VPN, GRE, IPSec, DMVPN, Zero Tier, PPTP, L2TP, Wire Guard
Casing	Aluminum Metal Casing, IP30
Dimension	91.4x92.4x31mm (Excludes Antennas and Mounting Accessories)
Installation	Wall-mount, DIN rail
Operating Temperature	-40°C-75°C
Storage Temperature	-40°C-85°C